

SM-AMC (Advanced Management Card) Network Protection Chassis

Telephone:
732-870-0800

Toll Free:
1-800-600-9656

Fax:
732-870-1912

Postal Address:
45 Memorial Parkway
Long Branch, New Jersey 07740
United States of America

Support:
support@shoremicro.com

Information:
info@shoremicro.com

Sales:
sales@shoremicro.com

PORT CARDS:

Model #: SM-2701C
Description: Advanced Copper Card

Model #: SM-2701F
Description: Fiber Card

Model #: SM-2701CS
Description: Standard Copper Card

Model #: SM-2701CF
Description: Copper to Fiber Card

Model #: SM-2701FB
Description: Fiber Card with Optical Bypass

Model #: SM-2701IO
Description: Contact Closure Card

Model #: SM-2701S
Description: RS-530 Serial Card

Model #: SM-2701RF
Description: RF Coaxial Card

Model #: SM-2701F10G
Description: 10G Fiber Card

Model #: SM-2801C
Description: Copper Bypass Card

Model #: SM-2801F
Description: Copper or Fiber Optical GBIC Bypass Card

Model #: SM-2801F10G
Description: Fiber Optical Bypass Card



PRODUCT DESCRIPTION:

The SM-AMC controls individual port cards, network and console connections and a display area with front panel controls located on the Network Protection Chassis. The Network Protection Chassis requires at least one port card and one supervisor card to operate. The SM-AMC agent port can be connected to any 10/100BaseT-capable switch port to provide management capability over the network. Management may be accomplished through SNMP or a SSH session from any network terminal. Status LEDs for the management port provide indications for link integrity, link data reception, and link data transmission. Note that the IP address of the Link Protector must be configured in order to initiate a SSH session or to utilize SNMP.

FIRMWARE FEATURES:

Advanced Management Card (SM-AMC):

- ◆ All Standard Management Card Features
- ◆ IPV6
- ◆ SSH V2
- ◆ SNMP V3
- ◆ Multi User
- ◆ GUI/www
- ◆ Support EXT I/O, SERIAL, RF Cards
- ◆ Syslog
- ◆ NTP
- ◆ DHCP
- ◆ FTP

Standard Management Card (SM-SMC):

- ◆ Bootp
- ◆ ICMP
- ◆ ARP
- ◆ TCP
- ◆ SNMP
- ◆ IP
- ◆ TFTP
- ◆ Telnet

DESIGN FEATURES:

SM-NPC-12:



Location: First Slot
Removable: Yes

SM-NPC-2:



Location: Internal
Removable: No

ADVANCED CONSOLE INTERFACE:

The console RJ-45 connector interface utilizes a standard "Cisco" style DB9/RJ45 console cable (Cisco P/N 72-3383-01). A console cable is not supplied with unit but may be ordered separately.

SUPERVISOR CARD INDICATORS:

TX LED	This LED flashes yellow to indicate that the Agent port is transmitting.
RX/LT LED	This LED is solid green to indicate a good 10/100 link signal has been detected on the Agent port. This LED blinks off if network activity is detected.
S1 LED	This status LED should be green under normal circumstances.
S2 LED	This status LED should be green under normal circumstances.