

AVAILABLE PORT CARDS:

- SM-2701C: Advanced 1G Copper
- SM-2701F: Advanced 1G Fiber
- SM-2701CF: Adv 1G Copper=>Fiber
- SM-2701CS: Standard Copper
- SM-2701FC: Adv Fiber=>Copper
- SM-2701FE: Advanced 100BaseX
- SM-2701IO: Contact Closure
- SM-2701S: Advanced RS-530 Serial
- SM-2701RF: RF Coaxial
- SM-2701RS: Adv RS-232 Async
- SM-2701F10G: 1/10G Fiber
- SM-2801C: Adv Copper Bypass
- SM-2801F: Adv Fiber SFP Bypass
- SM-2801F10G: 1/10G Fiber Bypass

Telephone: 732-870-0800

Toll Free: 800-600-9656

Fax: 732-870-1912


Postal Address:

45 Memorial Parkway
 Long Branch, New Jersey 07740
 USA

Support: support@shoremicro.com

Information: info@shoremicro.com

Sales: sales@shoremicro.com



PRODUCT DESCRIPTION:

Each SM-2701F fiber port card provides three LC style duplex connectors intended for connection to a primary, backup and a protected 1000BaseSX Ethernet port. Single mode (LX or ZX) versions are available by special order. An optional optical bypass is available between Primary and Protected ports.

The SM-2701F detects link activity and an alarm is generated if any link fails. If the primary link is lost, the NPS will automatically switch to the backup link. By default, the switch is completed within 100 milliseconds after link problem is detected. Once the primary link is restored, the server port will revert to the primary link automatically. The link may also be forced to switch to the backup port manually.

KEY BENEFITS:

- ◆ Auto Switch to Backup on Loss of Connectivity
- ◆ Auto Switch to Primary on Restoration of Connectivity
- ◆ Default Connection to Primary Link on Loss of Power via *Straight through Wire*® Technology with optional optical bypass module
- ◆ *Packet Spy*™ allows Switching to Backup on Loss of Traffic Flow
- ◆ External Watchdog trigger via SNMP
- ◆ Capability to Force Port to Backup Condition
- ◆ Enable/Disable of Automatic Switching (Manual Override)
- ◆ Fiber Physical Layer - 1000BaseSX, 1000BaseLX or ZX by special order

FIRMWARE FEATURES:

Corporate System (Base):	Enterprise System:
<i>Straight through Wire</i> ® Technology allows Zero Power Connectivity	All Corporate System Features
Normal Mode- Port Acts Independently	Mirror Mode - Cards Provide Dual Output
Group Mode- Ports Act as a Group	Slave Mode (Port)
Latch Mode- Stays in the Backup/Bypass state until Manual Restored	Slave Mode (Group)
Enhanced Latch Mode- Latch is Automatically Released on Failure of Backup Link	Fast End-to-End Switchover via Patented MAC Address Spoofing
Reverse Mode- Reversed Logic (Backup Ports are Default)	Total and Any Group Switch Modes
<i>Packet Spy</i> ™- Backup Switchover Triggered by Lack of Packets on Active Link	External Watchdog Scripting
CRC Error Reporting	Turbo High Speed switching

